

ALUMINUM BOAT TRAILER I-BEAM

6061-T6 B




A	X	B	C	D	LENGTH	WEIGHT/FT
3"	X	2.5"	.260"	.150"	20'	2.030#
3"	X	2.5"	.260"	.150"	24'	2.030#
4-1/2"	X	3.0"	.260"	.175"	14'	2.685#
4-1/2"	X	3.0"	.260"	.175"	16'	2.685#
4-1/2"	X	3.0"	.260"	.175"	17'	2.685#
4-1/2"	X	3.0"	.260"	.175"	18'	2.685#
4-1/2"	X	3.0"	.260"	.175"	18' 6"	2.685#
4-1/2"	X	3.0"	.260"	.175"	20'	2.685#
4-1/2"	X	3.0"	.260"	.175"	21'	2.685#
4-1/2"	X	3.0"	.260"	.175"	22'	2.685#
5-1/2"	X	3.5"	.280"	.195"	16'	3.524#
5-1/2"	X	3.5"	.280"	.195"	18'	3.524#
5-1/2"	X	3.5"	.280"	.195"	20'	3.524#
5-1/2"	X	3.5"	.280"	.195"	21'	3.524#
5-1/2"	X	3.5"	.280"	.195"	22'	3.524#
5-1/2"	X	3.5"	.280"	.195"	23'	3.524#
5-1/2"	X	3.5"	.280"	.195"	25'	3.524#
6-1/2"	X	4.0"	.310"	.220"	19'	4.561#
6-1/2"	X	4.0"	.310"	.220"	20'	4.561#
6-1/2"	X	4.0"	.310"	.220"	21'	4.561#
6-1/2"	X	4.0"	.310"	.220"	22'	4.561#
6-1/2"	X	4.0"	.310"	.220"	23'	4.561#
6-1/2"	X	4.0"	.310"	.220"	24'	4.561#
6-1/2"	X	4.0"	.310"	.220"	25'	4.561#
6-1/2"	X	4.0"	.310"	.220"	27'	4.561#
6-1/2"	X	4.0"	.310"	.220"	28'	4.561#
6-1/2"	X	4.0"	.310"	.220"	30'	4.561#
6-1/2"	X	4.0"	.310"	.220"	32'	4.561#
7-1/2"	X	4.375"	.350"	.230"	25'	5.584#
7-1/2"	X	4.375"	.350"	.230"	26'	5.584#
7-1/2"	X	4.375"	.350"	.230"	27'	5.584#
7-1/2"	X	4.375"	.350"	.230"	28'	5.584#
7-1/2"	X	4.375"	.350"	.230"	30'	5.584#
7-1/2"	X	4.375"	.350"	.230"	32'	5.584#
7-1/2"	X	4.375"	.350"	.230"	35'	5.584#
7-1/2"	X	4.375"	.350"	.230"	38'	5.584#
8"	X	5"	.410"	.300"	30'	7.080#
8"	X	5"	.410"	.300"	35'	7.080#
8"	X	5"	.410"	.300"	36'	7.080#
8"	X	5"	.410"	.300"	40'	7.080#

ALUMINUM STRUCTURAL I-BEAM

AMERICAN STANDARD [AS]

6061-T6, QQ-A-200/16



A	X	B	X	C	LENGTH	WEIGHT/FT
3"	X	2.330"	X	.170	25'	1.944#
3"	X	2.509"	X	.349	25'	2.670#
4"	X	2.660"	X	.190	25'	2.642#
5"	X	3.000"	X	.210	25'	3.508#
5"	X	3.284"	X	.494	25'	5.250#
6"	X	3.330"	X	.230	25'	4.421#
6"	X	3.443"	X	.343	25'	5.220#
6"	X	3.565"	X	.465	25'	6.072#
8"	X	4.000"	X	.270	25'	6.510#
10"	X	4.660"	X	.310	25'	8.981#
12"	X	5.000"	X	.350	25'	11.220#